

Ressorts de compression

Tolérance sur le diamètre suivant DIN 2095

Dm		Qualité 1 pour rapport d'enroulement W			Qualité 2 pour rapport d'enroulement W			Qualité 3 pour rapport d'enroulement W		
		4 ≤ 8	≥ 8 ≤ 14	> 14 ≤ 20	4 ≤ 8	≥ 8 ≤ 14	> 14 ≤ 20	4 ≤ 8	≥ 8 ≤ 14	> 14 ≤ 20
0,63	1	± 0.05	± 0.07	± 0.1	± 0.07	± 0.1	± 0.15	± 0.1	± 0.15	± 0.2
1	1,6	± 0.05	± 0.07	± 0.1	± 0.08	± 0.1	± 0.15	± 0.15	± 0.2	± 0.3
1,6	2,5	± 0.07	± 0.1	± 0.15	± 0.1	± 0.15	± 0.2	± 0.2	± 0.3	± 0.4
2,5	4	± 0.1	± 0.1	± 0.15	± 0.15	± 0.2	± 0.25	± 0.3	± 0.4	± 0.5
4	6,3	± 0.1	± 0.15	± 0.2	± 0.2	± 0.25	± 0.3	± 0.4	± 0.5	± 0.6
6,3	10	± 0.15	± 0.15	± 0.2	± 0.25	± 0.3	± 0.35	± 0.5	± 0.6	± 0.7
10	16	± 0.15	± 0.2	± 0.25	± 0.3	± 0.35	± 0.4	± 0.6	± 0.7	± 0.8
16	25	± 0.2	± 0.25	± 0.3	± 0.35	± 0.45	± 0.5	± 0.7	± 0.9	± 1.0
25	31,5	± 0.25	± 0.3	± 0.35	± 0.4	± 0.5	± 0.6	± 0.8	± 1.0	± 1.2
31,5	40	± 0.25	± 0.3	± 0.35	± 0.5	± 0.6	± 0.7	± 1.0	± 1.2	± 1.5
40	50	± 0.3	± 0.4	± 0.5	± 0.6	± 0.8	± 0.9	± 1.2	± 1.5	± 1.8
50	63	± 0.4	± 0.5	± 0.6	± 0.8	± 1.0	± 1.1	± 1.5	± 2	± 2.3
63	80	± 0.5	± 0.7	± 0.8	± 1.0	± 1.2	± 1.4	± 1.8	± 2.4	± 2.8
80	100	± 0.6	± 0.8	± 0.9	± 1.2	± 1.5	± 1.7	± 2.3	± 3	± 3.5
100	125	± 0.7	± 1.0	± 1.1	± 1.4	± 1.9	± 2.2	± 2.8	± 3.7	± 4.4
125	160	± 0.9	± 1.2	± 1.4	± 1.8	± 2.3	± 2.7	± 3.5	± 4.6	± 5.4
160	200	± 1.2	± 1.5	± 1.7	± 2.1	± 2.9	± 3.3	± 4.2	± 5.7	± 6.6

W = Diamètre moyen / diamètre fil

|